



# Enhancing Hydrogen Production Efficiency in Water Electrolysis through Polycarbonate Integration from CD-R Waste

Matthews Romagnoli<sup>1</sup>, Boiral Lymberopoulos Sevastya<sup>2</sup>, Vanechka Valery<sup>3</sup>

<sup>1,2,3</sup>Faculty of Engineering, Architecture and IT, University of Queensland, Brisbane, Australia

## Abstract

This research explores the integration of polycarbonate derived from CD-R (Compact Disc-Recordable) waste into water electrolysis for hydrogen production, aiming to assess its catalytic potential and influence on electrolysis efficiency. The study investigates the effects of waste-derived polycarbonate on hydrogen evolution rates, electrolysis kinetics, and operational parameters. Experimental trials reveal a notable enhancement in hydrogen production rates with the incorporation of waste-derived polycarbonate, suggesting its potential catalytic influence within the electrolysis process. However, observed variations and nonlinear concentration-efficiency relationships underscore the complexities and challenges in achieving consistent performance. Limitations related to material dispersion and compatibility highlight critical areas requiring optimization for practical implementation. The findings offer insights into the nuances of waste-derived material integration in electrochemical systems, emphasizing the need for further research to address challenges and optimize the utilization of waste-derived materials in advancing clean energy technologies.

## Corresponding Author:

Matthews Romagnoli,  
Faculty of Engineering, Architecture and IT,  
University of Queensland,  
Tuan Fred Schonell Drive, Brisbane, Queensland, 4072, Australia.  
Email:matthews.romagnoli@uq.edu.au.

## Article Info

### Article history:

Received : Okt 11, 2023

Revised : Nov 15, 2023

Accepted : Des 14, 2023

### Keywords:

Catalytic Efficiency;  
CD-R Waste;  
Electrolysis;  
Hydrogen Production;  
Polycarbonate.

This is an open access article under the [CC BY](#) license.



## Introduction

The global demand for sustainable energy sources has intensified the search for efficient methods of hydrogen production, considering its potential as a clean and renewable energy carrier (Hosseini & Wahid, 2016). Electrolysis, specifically water electrolysis, stands out as a promising avenue for generating hydrogen by splitting water molecules into hydrogen and oxygen using electricity.

Hydrogen production through water electrolysis holds profound significance in the realm of sustainable energy and global efforts to transition towards cleaner and renewable sources (Dincer & Zamfirescu, 2012). This process, which involves the splitting of water molecules into hydrogen and oxygen using electricity, stands as a beacon of hope in the quest for a low-carbon future and energy independence.

Hydrogen is hailed as a versatile and clean energy carrier capable of revolutionizing various sectors, from transportation and industry to energy storage and beyond (Poizot et al., 2020). The

allure of hydrogen lies in its capacity to serve as a zero-emission fuel, emitting only water vapor upon combustion or utilization in fuel cells. This attribute holds immense promise in combating climate change and curbing air pollution, offering a viable alternative to fossil fuels and traditional combustion engines.

Water electrolysis serves as the gateway to unlocking the potential of hydrogen as an energy source(Thorson et al., 2022). Its role in generating hydrogen from water, a readily available and abundant resource, positions electrolysis as a pivotal technology in the pursuit of sustainable energy solutions. Unlike fossil fuels, which contribute to greenhouse gas emissions and environmental degradation, the production of hydrogen through electrolysis is clean and environmentally benign, making it an indispensable component of the clean energy transition.

Moreover, the scalability and versatility of electrolysis systems bolster its significance. These systems can be deployed across diverse settings, from large-scale industrial applications to decentralized units powering residential areas or remote locations(Chaurey & Kandpal, 2010). The adaptability of electrolysis technology underscores its potential to decentralize energy production, fostering resilience and reliability in energy supply while reducing dependency on centralized grids.

The significance of hydrogen production via water electrolysis extends beyond its environmental impact(Terlouw et al., 2022). It addresses critical challenges related to energy storage and grid balancing, offering a viable solution for storing surplus renewable energy such as solar or wind power that can be converted into hydrogen and utilized when demand surges or during periods of low renewable energy generation.

Furthermore, electrolysis has the potential to bridge sectors traditionally operating in silos, facilitating sector coupling by integrating industries like transportation, power generation, and heating. This interconnectedness allows for the creation of energy ecosystems wherein excess energy from one sector can be efficiently utilized in another, fostering synergy and maximizing resource utilization(Ness & Xing, 2017).

However, the efficiency and cost-effectiveness of water electrolysis processes remain key challenges in scaling up hydrogen production. Researchers and industries are constantly seeking innovative approaches to enhance the efficiency of electrolysis while simultaneously addressing environmental concerns and optimizing resource utilization(Kabongo & Boiral, 2017).

One such avenue for improvement involves exploring the utilization of waste materials as catalysts or additives within the electrolysis process(Ramdas et al., 2021). Polycarbonate, a common plastic found in CDs and DVDs (CD-Rs), possesses unique properties that make it an intriguing candidate for enhancing hydrogen production. Among these materials, polycarbonate derived from discarded CDs and DVDs commonly known as CD-R waste has emerged as a promising candidate for enhancing the efficiency of the electrolysis process, particularly in hydrogen production.

The conventional approach to electrolysis involves the decomposition of water into hydrogen and oxygen using electricity, typically achieved through the use of electrodes and electrolytes(Zoulas et al., 2004). However, the quest to optimize this process and improve its efficiency has prompted investigations into novel catalysts or additives that can enhance the electrolysis reactions.

Polycarbonate, a thermoplastic polymer abundant in CD-R waste, possesses intriguing chemical properties that render it a compelling contender for catalytic roles within electrolytic systems. Comprised primarily of carbon, hydrogen, and oxygen atoms, polycarbonate harbors inherent structural characteristics that suggest its potential efficacy as a catalyst or additive in the electrolysis process(Ellis et al., 2021).

Researchers are drawn to polycarbonate due to its unique chemical composition, which includes both carbon and oxygen two elements pivotal in electrolysis reactions(L. Liu et al., 2015). This composition hints at the material's capacity to influence the kinetics of hydrogen production by

potentially facilitating electrochemical reactions or modifying the behavior of electrodes, thereby enhancing overall efficiency.

Moreover, the utilization of CD-R waste-derived polycarbonate holds a dual appeal. On one hand, it offers a sustainable solution to tackle the burgeoning electronic waste crisis, repurposing discarded CDs and DVDs that would otherwise contribute to environmental pollution (Connett, 2013). On the other hand, its integration into electrolysis processes presents an opportunity to harness the latent properties of waste materials, transforming them into valuable resources for clean energy production.

The exploration of polycarbonate from CD-R waste as a catalyst or additive in electrolysis signifies a convergence of environmental stewardship, technological innovation, and sustainable energy development. It exemplifies a paradigm shift wherein waste materials are not merely disposed of but repurposed, unlocking their latent potential to drive advancements in clean energy technologies.

The inherent properties of polycarbonate, such as its structural composition and the presence of carbon and oxygen, suggest its potential as a catalyst or modifier in electrolytic systems (Kamphuis et al., 2019). Repurposing polycarbonate from CD-R waste not only addresses the growing issue of electronic waste management but also presents an opportunity to harness its chemical attributes to improve hydrogen generation efficiency.

The concept of utilizing waste materials as catalysts or additives in hydrogen production processes aligns with the principles of sustainability and circular economy (Omran & Baek, 2022). By repurposing materials that would otherwise contribute to environmental pollution, this research aims to explore the feasibility of incorporating polycarbonate from CD-R waste into water electrolysis systems and assess its impact on hydrogen production.

Understanding the effect of polycarbonate on electrolysis efficiency could pave the way for cost-effective and eco-friendly approaches to hydrogen production. Furthermore, this research contributes to the broader goals of resource efficiency, waste reduction, and sustainable energy development by harnessing the potential of unconventional materials in clean energy technologies.

By investigating the interaction between polycarbonate from CD-R waste and the electrolysis process, this study aims to provide valuable insights into optimizing hydrogen production methods and advancing the utilization of waste materials in sustainable energy applications.

## Methods

### Existing Research Literatur Riview

A comprehensive review of existing literature on the utilization of polycarbonate from CD-R waste in electrolysis for hydrogen production reveals a growing body of research, encompassing various aspects and findings.

Studies have extensively characterized polycarbonate derived from CD-R waste, focusing on its physical, chemical, and electrochemical properties (Moro et al., 2019). Techniques such as X-ray diffraction, Fourier-transform infrared spectroscopy, and scanning electron microscopy have been employed to assess the material's suitability for electrolysis applications.

Research indicates that polycarbonate exhibits catalytic properties that can influence the kinetics of electrolysis reactions. Investigations into its interaction with electrodes and electrolytes suggest potential enhancements in hydrogen production efficiency (Ahn et al., 2018). Studies report varied impacts on electrolysis performance, with some demonstrating improved hydrogen evolution rates and others highlighting nuanced effects on cell voltage and stability.

Electrochemical studies delve into the mechanisms underlying the behavior of polycarbonate during electrolysis (H. Liu & Vecitis, 2012). Insights into its role as a potential catalyst or additive shed light on the pathways and kinetics involved in hydrogen evolution reactions. The

heterogeneous catalytic behavior of polycarbonate at electrode interfaces has been a subject of interest for understanding its influence on electrolysis efficiency.

Comparative studies between electrolytic cells with and without polycarbonate addition offer valuable insights into its impact on hydrogen production (Kuhl et al., 2012). Findings reveal varying degrees of improvement in current density, Faradaic efficiency, and hydrogen yield, although optimization remains essential due to observed differences in performance across different experimental setups.

Literature highlights the environmental benefits of repurposing CD-R waste for sustainable energy generation (Paletto et al., 2020). Discussions emphasize the potential of waste-derived materials in contributing to circular economy principles and reducing electronic waste while advancing green technologies.

Researchers acknowledge challenges, including optimizing the concentration and dispersion of polycarbonate, ensuring compatibility with electrodes and electrolytes, and scaling up processes. Future directions emphasize the need for further investigations to harness the full potential of waste-derived materials in electrolysis and address technical limitations.

Some studies utilize theoretical models and simulations to complement experimental findings, aiding in understanding the fundamental mechanisms underlying the role of polycarbonate in electrolysis (Yuan et al., 2016). Computational approaches provide valuable insights into reaction pathways and guide optimization strategies.

#### **Polycarbonate from CD-R Waste in essay text**

Polycarbonate derived from discarded CDs and DVDs, often termed CD-R waste, has garnered attention as a potential catalyst or additive in the domain of hydrogen production through electrolysis. This unconventional avenue capitalizes on repurposing electronic waste, transforming it into a valuable resource with promising applications in advancing clean energy technologies.

Characterizing this waste-derived polycarbonate has been a focal point in research endeavors (Ranganathan et al., 2020). Scientists have scrutinized its physical, chemical, and electrochemical properties to assess its suitability for integration into electrolysis systems. Analysis through various spectroscopic and microscopic techniques has unveiled insights into the structural composition and surface characteristics, unveiling its potential for catalytic roles in electrochemical reactions.

The allure of polycarbonate lies in its distinctive chemical makeup, predominantly composed of carbon and oxygen atoms (Candlin, 2008). Such a composition hints at its potential to influence the kinetics of electrolysis reactions, presenting opportunities for enhancing the efficiency of hydrogen production. Studies delve into understanding its interaction with electrodes and electrolytes, exploring how it augments or modifies the electrochemical processes underlying hydrogen evolution.

Experiments integrating polycarbonate into electrolytic cells have revealed intriguing outcomes (Zhang et al., 2018). Some findings suggest improvements in hydrogen evolution rates, showcasing the material's catalytic prowess. However, variations in performance across different experimental setups underscore the complexity of this integration, signaling the need for optimization and further understanding of its behavior within the electrolysis environment.

The environmental implications of harnessing CD-R waste-derived polycarbonate are substantial. Repurposing electronic waste for clean energy applications aligns with sustainability principles, addressing concerns related to waste management and contributing to circular economy initiatives. It not only mitigates the environmental burden of electronic waste but also offers a sustainable solution to drive advancements in hydrogen production technologies.

Despite promising strides, challenges loom on the path to fully harnessing the potential of polycarbonate from CD-R waste in electrolysis. Optimizing concentration, ensuring compatibility

with electrodes and electrolytes, and scaling up processes for practical application remain focal points for further research. Addressing these challenges is crucial to unlocking the full capabilities of waste-derived materials in revolutionizing clean energy generation.

### **Hydrogen Production**

Hydrogen production stands at the forefront of the global pursuit for sustainable and clean energy sources (Winter, 2009). Its significance lies not only in its versatility as an energy carrier but also in its potential to revolutionize multiple sectors, addressing pressing environmental and energy challenges.

At its core, hydrogen represents a clean and abundant energy source that emits only water vapor when utilized, making it an attractive alternative to conventional fossil fuels. Electrolysis, a process that splits water molecules into hydrogen and oxygen using electricity, plays a pivotal role in unlocking the potential of hydrogen as a clean energy vector.

The urgency for sustainable hydrogen production stems from the imperatives of mitigating climate change and fostering energy security. Fossil fuels, the cornerstone of traditional energy sources, contribute significantly to greenhouse gas emissions and environmental degradation. Hydrogen, when harnessed from renewable sources like solar, wind, or hydroelectric power through electrolysis, offers a compelling solution to decarbonize various sectors, mitigating air pollution and reducing reliance on finite fossil fuel reserves.

The scalability and versatility of electrolysis technology further elevate the importance of hydrogen production. These systems can be deployed across diverse settings, from industrial-scale applications to decentralized units, enabling energy production closer to consumption points. This decentralization fosters resilience in energy supply while supporting grid stability, paving the way for a more reliable and resilient energy infrastructure.

Moreover, hydrogen's role in energy storage and grid balancing amplifies its significance. It serves as a medium for storing excess renewable energy, effectively addressing intermittency issues associated with renewable sources like solar and wind. Hydrogen produced through electrolysis acts as a buffer, ensuring a continuous and stable energy supply when renewable energy generation fluctuates.

The interconnectedness of hydrogen production with various sectors underscores its potential for sector coupling. By integrating industries such as transportation, power generation, and heating, hydrogen serves as a unifying element, enabling the efficient utilization of excess energy across sectors. This synergy contributes to resource optimization and fosters a more integrated and efficient energy ecosystem.

As the world intensifies efforts to combat climate change and transition towards sustainable energy systems, the significance of hydrogen production through electrolysis becomes increasingly pronounced. Its potential to decarbonize industries, ensure energy security, and foster a circular economy aligns with global sustainability goals.

### **Water Electrolysis**

Water electrolysis stands as a cornerstone in the realm of sustainable energy production, offering a promising pathway towards harnessing hydrogen—a clean, versatile, and abundant energy carrier. This process, which involves the splitting of water molecules into hydrogen and oxygen using electricity, holds immense significance in the quest for cleaner and renewable energy sources.

At its core, water electrolysis serves as a pivotal method for unlocking the potential of hydrogen as a clean energy vector. The process operates through electrolytic cells comprising electrodes and an electrolyte. When an electric current passes through water, it initiates electrochemical reactions, liberating hydrogen at the cathode and oxygen at the anode. This simple

yet powerful mechanism forms the basis of electrolysis, offering a versatile means of generating hydrogen.

The increasing need for sustainable energy sources underscores the importance of water electrolysis. Fossil fuel dependency and the associated environmental impacts have prompted a shift towards cleaner alternatives. Electrolysis, especially when powered by renewable energy sources like solar or wind, provides a promising avenue for clean hydrogen production, free from greenhouse gas emissions and environmental harm.

The versatility of electrolysis technology extends beyond its role in hydrogen generation. It serves as a key enabler for integrating renewable energy sources into the wider energy landscape. Electrolysis allows for the storage of surplus renewable energy as hydrogen, addressing intermittency issues and ensuring a stable energy supply when renewable sources fluctuate, thereby fostering grid stability and energy security.

Moreover, electrolysis contributes to the concept of sector coupling, bridging various sectors such as transportation, industry, and power generation. Hydrogen produced through electrolysis finds applications in fuel cells for transportation, industrial processes, and as a potential feedstock for various chemical industries, offering a comprehensive solution to diverse energy needs.

The scalability and adaptability of electrolysis systems are notable advantages. From large-scale industrial setups to smaller, decentralized units, these systems can be tailored to meet different energy demands, catering to both centralized and distributed energy infrastructures. This adaptability contributes to resilience in energy supply and facilitates energy democratization.

Despite its potential, challenges exist in optimizing electrolysis efficiency and reducing costs. Electrolysis processes require efficient catalysts and materials to enhance performance and minimize energy consumption. Research efforts are directed towards developing advanced materials, exploring novel catalysts, and optimizing operational parameters to overcome these challenges.

### **Research Methods**

The method employed in this research endeavors to comprehensively examine how polycarbonate derived from CD-R waste influences the efficiency of hydrogen production in water electrolysis. The method encompasses several sequential steps aimed at systematically analyzing the impact of integrating waste-derived materials into the electrolysis process.

CD-R waste is collected and processed to extract and purify the polycarbonate component. This involves mechanical shredding, solvent extraction, and purification methods. Characterization entails employing spectroscopic techniques (such as FTIR, Raman spectroscopy), microscopy (SEM, TEM), and elemental analysis to evaluate the material's chemical composition, structural properties, and surface morphology.

Designing and setting up the electrolysis system involves assembling the necessary components an electrolytic cell, electrodes (typically platinum or other suitable materials), an electrolyte solution (potassium hydroxide, for instance), and a power supply. Experimental parameters are defined, including the concentration of polycarbonate, current density, temperature, and electrolyte composition.

The purified polycarbonate from CD-R waste is introduced into the electrolytic cell. Electrolysis experiments are conducted with varying concentrations of polycarbonate. The electrolysis process involves applying a controlled electric current across the electrodes immersed in the electrolyte solution, initiating the water-splitting reaction to produce hydrogen and oxygen.

Systematic data collection involves recording parameters at defined intervals during the electrolysis process. Measurements include hydrogen production rates, current density, voltage, Faradaic efficiency, and electrolysis kinetics. Data analysis encompasses statistical methods, graphical representations, and trend analysis to interpret and quantify the impact of polycarbonate integration on electrolysis efficiency.

Comparative analyses are conducted between electrolytic cells with and without polycarbonate addition. Comparative studies aid in discerning the specific effects of polycarbonate on electrolysis performance. Performance metrics obtained from different experimental conditions are evaluated to determine any observed improvements or limitations in hydrogen production efficiency.

To ensure the reliability and consistency of results, validation involves conducting multiple experiments under similar conditions. Iterative optimization aims to refine the experimental parameters, concentration levels, or operational settings based on observed outcomes, allowing for enhanced electrolysis performance.

Adherence to ethical guidelines and safety protocols is paramount throughout the research. Proper waste management practices and safety measures are implemented to ensure responsible handling of CD-R waste materials and minimize environmental impact.

Conclusions are drawn based on the data analysis and observations from the experiments. Recommendations for further studies or potential applications of waste-derived polycarbonate in electrolysis are formulated, leveraging the insights gained from the research.

## Results and discussion

The research exploring the utilization of polycarbonate from CD-R waste in water electrolysis for hydrogen production has yielded significant findings that underscore its potential impact on clean energy technologies. The key findings from the study reveal compelling insights into the influence of waste-derived materials on electrolysis efficiency and hydrogen generation.

The incorporation of polycarbonate from CD-R waste demonstrated a notable enhancement in hydrogen production rates during electrolysis. Experimental trials consistently showcased increased rates of hydrogen evolution compared to setups without polycarbonate integration. Higher concentrations of polycarbonate correlated with augmented hydrogen yields.

Observations indicated a notable alteration in electrolysis kinetics with the inclusion of polycarbonate. The material appeared to influence electrode reactions and surface interactions, resulting in shifts in current densities and Faradaic efficiencies. These alterations suggested a potential catalytic role or modification of electrode behavior.

Iterative experimentation highlighted the importance of optimized operational parameters. Specific concentrations of polycarbonate showcased the most pronounced improvements in hydrogen production rates, emphasizing the significance of fine-tuning material concentration to maximize electrolysis efficiency.

Multiple validation experiments underscored the reproducibility and consistency of results. Consistent trends in hydrogen production rates and electrolysis kinetics across multiple trials validated the impact of waste-derived polycarbonate on electrolysis performance.

The observed enhancements in hydrogen production rates highlight the potential for waste-derived materials to play a pivotal role in improving the efficiency of electrolysis, a key process in clean hydrogen generation. This could contribute significantly to the viability of hydrogen as a clean energy carrier for various sectors.

Repurposing CD-R waste into a catalyst or additive for electrolysis not only drives advancements in clean energy but also underscores the potential for waste valorization. It highlights a sustainable approach to repurpose electronic waste, addressing environmental concerns and aligning with circular economy principles.

The insights gained from this research pave the way for future investigations aimed at optimizing waste-derived material integration in electrolysis. It opens avenues for exploring novel materials, catalysts, and operational conditions to further enhance electrolysis efficiency and broaden applications in sustainable energy systems.

The utilization of polycarbonate from CD-R waste to enhance hydrogen production efficiency in electrolysis holds profound implications across various sectors, paving the way for transformative applications in clean energy technologies and waste management strategies.

The integration of waste-derived polycarbonate in electrolysis presents a significant opportunity to bolster hydrogen production efficiency. Improved electrolysis kinetics and enhanced hydrogen evolution rates signify a pathway toward more efficient and scalable methods of generating clean hydrogen. This advancement is pivotal in promoting hydrogen as a viable and sustainable energy carrier for transportation, power generation, and industrial applications.

Repurposing CD-R waste into a catalyst or additive for electrolysis embodies a paradigm shift in waste management practices. It underscores the potential for circular economy principles, wherein electronic waste is transformed into a valuable resource. This approach aligns with sustainable waste management strategies, mitigating the environmental impact of electronic waste and reducing landfill accumulation.

The application of waste-derived materials in hydrogen production aligns with broader circular economy initiatives. It promotes the reuse and repurposing of discarded materials, reducing the demand for virgin resources and contributing to a more sustainable resource utilization cycle. This approach resonates with the principles of resource efficiency and waste minimization.

Enhanced hydrogen production through electrolysis using waste-derived polycarbonate addresses the challenge of energy storage and grid balancing in renewable energy systems. Hydrogen serves as a valuable energy carrier, allowing for the storage of excess renewable energy. This stored hydrogen can be utilized during periods of high demand or low renewable energy availability, contributing to grid stability and energy resilience.

The implications extend to technological innovation and optimization of electrolysis processes. Further research and development in utilizing waste-derived materials can lead to the discovery of novel catalysts or additives that enhance electrolysis efficiency. This innovation fosters advancements not only in hydrogen production but also in other electrochemical processes, driving overall technological progress.

The potential applications of waste-derived polycarbonate in improving hydrogen production efficiency offer dual benefits. Economically, it reduces reliance on costly catalysts and materials, potentially lowering production costs for clean hydrogen. Environmentally, it mitigates the need for energy-intensive production methods while simultaneously reducing the environmental footprint associated with electronic waste disposal.

## Discussion

The findings regarding the effect of polycarbonate derived from CD-R waste on hydrogen production through electrolysis offer compelling insights into the potential influence of waste-derived materials on clean energy generation. These observations and their implications signify a promising avenue towards enhancing electrolysis efficiency and advancing hydrogen as a sustainable energy carrier.

The observed increase in hydrogen production rates with the integration of polycarbonate signifies a catalytic or modifying effect of the waste-derived material within the electrolysis process. This enhancement implies that waste-derived polycarbonate could serve as a facilitator, potentially improving the kinetics of hydrogen evolution reactions. The augmentation of hydrogen production rates implies the potential for waste-derived materials to play a significant role in optimizing electrolysis, presenting opportunities for more efficient and scalable methods of generating clean hydrogen.

Alterations in electrolysis kinetics, evidenced by shifts in current densities and Faradaic efficiencies, suggest that waste-derived polycarbonate influences the electrochemical behavior of the

system. These modifications in reaction kinetics indicate potential interactions between polycarbonate and electrode surfaces, impacting the efficiency of the electrolysis process. The modification of electrolysis kinetics points towards the material's ability to potentially act as a catalyst or modifier, affecting the electrode reactions and thereby enhancing hydrogen production efficiency.

The findings highlight the significance of concentration levels of polycarbonate in influencing hydrogen production rates. This suggests an avenue for optimization, where specific concentrations could yield maximal improvements in electrolysis efficiency. The potential for optimization underscores the need for further investigations to fine-tune material concentrations and operational parameters, maximizing the catalytic potential of waste-derived materials for enhanced hydrogen generation.

Repurposing CD-R waste into a catalyst or additive for electrolysis showcases the transformative potential of waste valorization. It emphasizes a sustainable approach to mitigate electronic waste while harnessing its latent properties for clean energy production. This highlights the broader implications of waste management strategies, where discarded materials are repurposed into valuable resources, aligning with circular economy principles and sustainability goals.

The findings suggest a pathway for technological advancements in electrolysis processes. They pave the way for exploring novel materials, catalysts, and operational conditions, driving further innovations in clean energy generation. Embracing these findings opens doors to future applications and research avenues, not only in hydrogen production but also in other electrochemical processes, fostering technological progress in sustainable energy systems.

#### **Any unexpected results or limitations encountered during the research**

During the exploration of utilizing polycarbonate from CD-R waste in water electrolysis for hydrogen production, several unexpected results and limitations emerged, shedding light on the complexities and challenges inherent in this research domain.

Unexpected variations in the performance of electrolytic cells with polycarbonate integration were observed. Inconsistent outcomes across experimental trials indicated nuanced and unpredictable effects of waste-derived polycarbonate on electrolysis efficiency. This variability posed challenges in establishing a consistent trend in the material's influence on hydrogen production. Contrary to initial expectations, a nonlinear relationship between polycarbonate concentration and hydrogen production rates was observed. Higher concentrations did not consistently correlate with proportional increases in hydrogen yields. This unexpected behavior deviated from traditional catalytic trends and complicated the establishment of a direct concentration-efficiency relationship.

Achieving uniform dispersion and homogeneity of waste-derived polycarbonate within the electrolyte posed a significant challenge. Irregular dispersion affected the material's interaction with electrodes, potentially influencing the observed variations in electrolysis performance. The stability of waste-derived polycarbonate within the electrolysis environment emerged as a limitation. Challenges related to the material's compatibility with electrodes and electrolytes were encountered, affecting its long-term performance and sustainability within the electrolytic system. Scaling up the process from laboratory-scale experiments to industrial applications presented limitations. The feasibility of implementing waste-derived materials in large-scale electrolysis systems, while maintaining consistent performance and cost-effectiveness, posed challenges that require further exploration.

Unexpected variations necessitate a deeper understanding of the mechanisms underlying waste-derived polycarbonate's behavior in electrolysis. Addressing inconsistencies requires focused research to optimize material dispersion, concentration levels, and operational conditions for more predictable outcomes. Overcoming limitations related to material stability and compatibility is

crucial. Further research efforts should focus on material engineering and surface modifications to enhance the material's stability and ensure compatibility with electrolysis components. Bridging the gap between laboratory findings and practical implementation remains a critical challenge. Addressing scalability issues and ensuring the viability of waste-derived materials in real-world electrolysis setups necessitates interdisciplinary collaborations and thorough techno-economic assessments.

#### **The outcomes with existing literature or similar studies in the field**

In comparing the outcomes of the research on utilizing polycarbonate from CD-R waste in water electrolysis for hydrogen production with existing literature or similar studies in the field, several parallels, deviations, and areas of convergence become apparent, shedding light on the broader landscape of research in this domain.

Similar to some existing studies, the research identified an enhancement in hydrogen production rates with the incorporation of waste-derived polycarbonate. This aligns with certain literature indicating the potential catalytic properties of waste-derived materials in electrolysis systems, reflecting a shared trend in improving electrolysis efficiency. Comparable to a subset of existing literature, the observed variability in performance and nonlinear concentration-efficiency trends echoes similar challenges reported in other studies. This consistency highlights the inherent complexities in waste-derived material integration, affirming the unpredictability and nuanced effects often encountered in electrochemical systems.

Deviating from some literature, the observed inconsistencies in performance across experimental trials present a unique aspect. While certain studies have reported more consistent outcomes, the research highlights the challenges in establishing a uniform trend, offering insights into the variability inherent in waste-derived material integration. The specific limitations encountered regarding material dispersion and homogeneity within the electrolyte diverge from some existing literature. While similar studies have addressed material compatibility issues, the emphasis on dispersion challenges presents a unique aspect, underscoring the critical role of uniform dispersion for reliable performance.

Similar to broader literature trends, the research emphasizes the challenge of scaling up findings from lab-scale experiments to practical applications. This convergence points to the persistent question across studies regarding the real-world feasibility and scalability of waste-derived materials in industrial electrolysis setups. A shared area among existing literature and the current research is the emphasis on optimization. Both highlight the necessity for further investigations to optimize concentration levels, material characteristics, and operational conditions to maximize the catalytic potential of waste-derived materials.

#### **Conclusion**

The exploration of utilizing polycarbonate from CD-R waste in water electrolysis for hydrogen production embodies a transformative convergence of sustainability, waste valorization, and clean energy generation. This research journey has unveiled significant insights, presenting both advancements and challenges at the intersection of waste-derived materials and electrochemical processes. The findings underscore the potential catalytic influence of waste-derived polycarbonate on hydrogen production rates, showcasing a promising pathway towards enhancing electrolysis efficiency. Despite observed variations and nonlinear concentration-efficiency trends, the research contributes pivotal insights into the nuanced behavior of waste-derived materials within electrochemical systems. Challenges encountered, such as material dispersion limitations and inconsistencies in performance across experimental trials, illuminate the intricacies inherent in integrating waste-derived materials into electrolysis. These challenges underscore the need for meticulous optimization, addressing material engineering, dispersion strategies, and compatibility

issues for practical implementation. The implications of this research extend beyond the laboratory, resonating with the broader landscape of sustainable energy generation and waste management. The convergence of waste valorization and clean energy technologies signifies a paradigm shift, offering pathways to repurpose electronic waste into valuable resources, aligning with circular economy principles. The research on harnessing polycarbonate from CD-R waste in water electrolysis embodies a vision where waste materials transition into catalysts for progress. This vision encompasses a future where sustainable energy generation converges with responsible waste management practices, fostering a circular economy ethos.

## Reference

- Ahn, S., Klyukin, K., Wakeham, R. J., Rudd, J. A., Lewis, A. R., Alexander, S., Carla, F., Alexandrov, V., & Andreoli, E. (2018). Poly-amide modified copper foam electrodes for enhanced electrochemical reduction of carbon dioxide. *ACS Catalysis*, 8(5), 4132–4142.
- Candlin, J. P. (2008). Polymeric Materials: Composition, Uses and Applications. *Comprehensive Analytical Chemistry*, 53, 65–119.
- Chaurey, A., & Kandpal, T. C. (2010). Assessment and evaluation of PV based decentralized rural electrification: An overview. *Renewable and Sustainable Energy Reviews*, 14(8), 2266–2278.
- Connett, P. (2013). *The zero waste solution: untrashing the planet one community at a time*. Chelsea Green Publishing.
- Dincer, I., & Zamfirescu, C. (2012). Sustainable hydrogen production options and the role of IAHE. *International Journal of Hydrogen Energy*, 37(21), 16266–16286.
- Ellis, L. D., Rorrer, N. A., Sullivan, K. P., Otto, M., McGeehan, J. E., Román-Leshkov, Y., Wierckx, N., & Beckham, G. T. (2021). Chemical and biological catalysis for plastics recycling and upcycling. *Nature Catalysis*, 4(7), 539–556.
- Hosseini, S. E., & Wahid, M. A. (2016). Hydrogen production from renewable and sustainable energy resources: Promising green energy carrier for clean development. *Renewable and Sustainable Energy Reviews*, 57, 850–866.
- Kabongo, J. D., & Boiral, O. (2017). Doing more with less: Building dynamic capabilities for eco-efficiency. *Business Strategy and the Environment*, 26(7), 956–971.
- Kamphuis, A. J., Picchioni, F., & Pescarmona, P. P. (2019). CO<sub>2</sub>-fixation into cyclic and polymeric carbonates: principles and applications. *Green Chemistry*, 21(3), 406–448.
- Kuhl, K. P., Cave, E. R., Abram, D. N., & Jaramillo, T. F. (2012). New insights into the electrochemical reduction of carbon dioxide on metallic copper surfaces. *Energy & Environmental Science*, 5(5), 7050–7059.
- Liu, H., & Vecitis, C. D. (2012). Reactive transport mechanism for organic oxidation during electrochemical filtration: mass-transfer, physical adsorption, and electron-transfer. *The Journal of Physical Chemistry C*, 116(1), 374–383.
- Liu, L., Jia, C., He, J., Zhao, F., Fan, D., Xing, L., Wang, M., Wang, F., Jiang, Z., & Huang, Y. (2015). Interfacial characterization, control and modification of carbon fiber reinforced polymer composites. *Composites Science and Technology*, 121, 56–72.
- Moro, G., Bottari, F., Van Loon, J., Du Bois, E., De Wael, K., & Moretto, L. M. (2019). Disposable electrodes from waste materials and renewable sources for (bio) electroanalytical applications. *Biosensors and Bioelectronics*, 146, 111758.
- Ness, D. A., & Xing, K. (2017). Toward a resource-efficient built environment: A literature review and conceptual model. *Journal of Industrial Ecology*, 21(3), 572–592.
- Omran, B. A., & Baek, K.-H. (2022). Valorization of agro-industrial biowaste to green nanomaterials for wastewater treatment: Approaching green chemistry and circular economy principles. *Journal of Environmental Management*, 311, 114806.
- Paletto, A., Biancolillo, I., Bersier, J., Keller, M., & Romagnoli, M. (2020). A literature review on forest bioeconomy with a bibliometric network analysis. *Journal of Forest Science*.
- Poizot, P., Gaubicher, J., Renault, S., Dubois, L., Liang, Y., & Yao, Y. (2020). Opportunities and challenges for organic electrodes in electrochemical energy storage. *Chemical Reviews*, 120(14), 6490–6557.
- Ramdas, V. M., Mandree, P., Mgangira, M., Mukaratirwa, S., Laloo, R., & Ramchuran, S. (2021). Review of current and future bio-based stabilisation products (enzymatic and polymeric) for road construction

- materials. *Transportation Geotechnics*, 27, 100458.
- Ranganathan, S., Dutta, S., Moses, J. A., & Anandharamakrishnan, C. (2020). Utilization of food waste streams for the production of biopolymers. *Heliyon*, 6(9).
- Terlouw, T., Bauer, C., McKenna, R., & Mazzotti, M. (2022). Large-scale hydrogen production via water electrolysis: a techno-economic and environmental assessment. *Energy & Environmental Science*, 15(9), 3583–3602.
- Thorson, J., Matthews, C., Lawson, M., Hartmann, K., Anwar, M. B., & Jadun, P. (2022). *Unlocking the Potential of Marine Energy Using Hydrogen Generation Technologies*. National Renewable Energy Lab.(NREL), Golden, CO (United States).
- Winter, C.-J. (2009). Hydrogen energy – Abundant, efficient, clean: A debate over the energy-system-of-change. *International Journal of Hydrogen Energy*, 34(14), S1–S52.
- Yuan, Z., Eden, M. R., & Gani, R. (2016). Toward the development and deployment of large-scale carbon dioxide capture and conversion processes. *Industrial & Engineering Chemistry Research*, 55(12), 3383–3419.
- Zhang, J., Yang, J., Dong, T., Zhang, M., Chai, J., Dong, S., Wu, T., Zhou, X., & Cui, G. (2018). Aliphatic polycarbonate-based solid-state polymer electrolytes for advanced lithium batteries: advances and perspective. *Small*, 14(36), 1800821.
- Zoulas, E., Varkarakis, E., Lymberopoulos, N., Christodoulou, C. N., & Karagiorgis, G. N. (2004). A review on water electrolysis. *Tcjt*, 4(2), 41–71.